

JAPAN OIL 4T 15W-50 SM-MA 2 PURPLE

Product Description and Field of Use

High-tech synthetic motorcycle oil, formulated to provide full responsiveness from the engine and superior protection for all 4-stroke modern motorcycle. It can be used safely in high performance motorcycle.

Properties and Benefits

- Provides minimum vibration and noise due to excellent viscosity stability,
- Provides smoother clutch coupling and gear change due to low friction and oxidation performance,
- Enhanced responsiveness and efficient power delivery in the engine by excellent lubrication performance, especially at high operating temperatures,
- A long lasting oil film providing outstanding performance in all traffic conditions and temperatures.

Specifications and Approvals Fulfilled

API SM, JASO MA2

Typical Properties*

<u>TEST</u>	<u>UNIT</u>	<u>TEST METHOD</u>	<u>TYPICAL VALUES</u>
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	16.3-21.9
Viscosity Index		ASTM D 2270	130
Flashing Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-27

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.