

JAPAN OIL ATF 9 HP

Product Description and Field of Use

Bi-POWER ATF 9 HP 100% Synthetic is an energy-saving fluid made with the PAO base and innovative technology, patented by the Japanese company chemicals, to meet the requirements of modern ZF 9-speed automatic transmissions.

Properties and Benefits

- Dependable anti-wear and gear protection
- Synthetic base fluids
- Low temperature performance
- Exceptionally high oxidation resistance

Specifications and Approvals Fulfilled

ZF Lifeguard Fluid 9 Speed, ZF Lifeguard Fluid 6 / 8 Speed, ZF S671 090 312 / AA01.500.001, BMW ATF 3+, BMW L12108 (83 22 2 152 426), BMW 83 22 2 289 720, VW Group G 060 162, VW Group G 055 162, LAND ROVER LR 023288, LAND ROVER LR 023289, JAGUAR 02JDE 26444, HONDA / ACURA ATF-TYPE 3.1, HONDA 08200-9017, HONDA 08263-999-01HE, HONDA / ACURA ATF TYPE 3.0, HONDA / ACURA 08200-9016A, CHRYSLER 68157995AA, FIAT 9.55550-AV5, MOPAR 68218925AA, MOPAR 68157995AB, MOPAR ZF 8 & 9 SPEED ATF

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.86
K. Viscosity, @ 100°C	cSt	ASTM D 445	7,2
Viscosity Index		ASTM D 2270	150
Flashing Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-42

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.