

JAPAN OIL ATF CVT NS-3 GREEN

Product Description and Field of Use

CVT Fluid is high performance, continuously variable transmission fluid designed to meet the service fill use for many Japanese designed vehicles. CVT Fluid provides smoother, consistent all weather step-less shifting, and all-around lubrication protection of the transmission components to help extend transmission service life and provide a smooth driving experience.

Properties and Benefits

- Higher torque capacity,
- Advanced wear protection in thrust belt-pulley interface,.
- Superior operational efficiency with reduced risk of belt slipping,
- Provides improved oxidative stability with excellent viscosity control.

Specifications and Approvals Fulfilled

NISSAN CVT FLUID NS-3, NISSAN CVT FLUID NS-2, SUZUKI CVT FLUID GREEN 1GM/SATURN(DEX-CVT), MB.236.2, TOYOTA CVT FLUID TC, MITSUBISHI DIAQUEEN CVT FLUID J1, MITSUBISHI CVT ATF SP-II, MAZDA CVT FLUID 3320, HYUNDAI/KIA(SP-II), SUZUKI SCVT FLUID, SUZUKI CVT FLUID 1, SUBARU I-CVT FLUID, SUBARU I-CVT FLUID FG, DAIHATSU AMIX CVT FLUID DC, FORD CVT FLUID 23, GM/SATURN (DEX-CVT), MERCEDES-BENZ 235.20, MINI COOPER EZL 799A.

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	6.5-8
Viscosity Index		ASTM D 2270	179
Flashing Point	°C	ASTM D 92	205
Pour Point	°C	ASTM D 97	-48

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.